

LOADER S-2224

SPECIFICATIONS:-

Max. Operating Height : 3360 mm
 Pin Height : 2780 mm
 Load Over Height : 2540 mm
 Full Dump Height : 2220 mm
 Bucket Rated Capacity : 0.3 m³
 Safe Working Load : 300 Kg.



- Counter Weight Mount On Three Point Linkage.
- Loader Operated By Tractor Hydraulic System.

- Counter Weight Mount On Three Point Linkage.
- Loader Operated By Tractor Hydraulic System.



**LOADER S-2219
STANDARD BUCKET**

SPECIFICATIONS:-

Max. Operating Height : 4400 mm
 Pin Height : 3700 mm
 Load Over Height : 3420 mm
 Full Dump Height : 2930 mm
 Bucket Rated Capacity : 0.45/0.50 m³
 Safe Working Load : 500/800 Kg.



SIX-IN-ONE



GRAB BUCKET



SUGARCANE GRABBER



PALLET FORK

S-2212 S-2212II
 Max. Operating Height : 4290/4520 mm
 Pin Height : 3440/3700 mm
 Load Over Height : 3240/3420 mm
 Full Dump Height : 2700/3420 mm
 Bucket Rated Capacity : 0.65/0.65 m³
 Safe Working Load : 950/950 Kg.

S-2212 S-2212II
 Max. Operating Height : 4420/4650 mm
 Pin Height : 3440/3700 mm
 Load Over Height : 3240/3420 mm
 Full Dump Height : 2700/2930 mm
 Bucket Rated Capacity : 0.7/0.7 m³
 Safe Working Load : 900/900 Kg.

S-2212 S-2212II
 Max. Operating Height : 6270 mm
 Pin Height(Graber Arm Jaw) : 5390 mm
 Load Over Height : 4765 mm
 Reach At Dump : 1800 mm
 Safe Working Load : 550 Kg.

S-2212 S-2212II
 Pin Height : 3440/3700 mm
 Load Over Height : 3240/3420 mm
 Safe Working Load : 1050 kg.

LOADER S-2212 II
(Hi - Dump Bucket)



LOADER S-2212
(Hi - Dump Bucket)



SPECIFICATIONS	STANDARD BUCKET		HI - DUMP BUCKET	
	S-2212 II	S-2212	S-2212 II	S-2212
Max. Operating Height	4400 mm	4200 mm	4950 mm	4860 mm
Pin Height	3700 mm	3440 mm	4375 mm	4170 mm
Load Over Height	3420 mm	3240 mm	4298 mm	4100 mm
Full Dump Height	2930 mm	2700 mm	4200 mm	4030 mm
Bkt. Rated Capacity	0.65 cu.m.	0.65 cu.m	0.65 cu.m.	0.65 cu.m
Safe Working Load	1050 KG.	1050 KG.	950 KG.	950 KG.

- Counter Weight Mount On Chassis.
- Loader Operated By Independent Hydraulic System

LOADER BACKHOE S-2216
(Standrad Bucket)



SPECIFICATIONS OF BACKHOE:-

Max. Operating Height : 5490 mm
 Load Over Height : 4060 mm
 Digging Depth : 2500 mm
 Maximum Reach : 4350 mm
 Bucket Rated Capacity : 0.18 m³

SPECIFICATIONS OF LOADER:-

Max. operating Height : 4200 mm
 Pin Height : 3440 mm
 Load Over Height : 3240 mm
 Full Dump Height : 2700 mm
 Bucket Rated Capacity : 0.65 cu.m
 Safe Working Load : 1050 kg

Mfd. By:- SEC-RJMT ENGINEERING PVT. LTD.



Office: Plot No. 2, Pyala Road, Seekri, Opp. - Shiv Mandir, Ballabgarh - 121004
 Faridabad (HR). Contact No. : 0129 - 2215050/40

E-Mail: marketing@secrjmt.com, secrjmt1@rediffmail.com Website : www.secrjmt.com