

RJMT

LOADERS - BACKHOES - GRADERS

INNOVATION FOR BETTER OUTPUT

POWERFUL ATTACHMENTS FOR SONALIKA TRACTORS

LOADER S - 2212 II HI - DUMP BUCKET



Counter Weight Mounted Chassis.
Loader Operated By Independent Hydraulic System.

LOADER BACKHOE S-2216 HI - DUMP BUCKET



S.N	Attachments	Model	Tractor Reference		Hydraulic Operation	Bucket Inside Length (mm)	Rated Bucket Capacity (Cu.m)	Safe Working Load (kg)	Full Dump Height	Max. Opt. Height	Canopy YES/NO	Counter Weight On
			H.P.	Drive								
1	Standard Bucket	S 2212 II	55-65	2WD/4WD	Tr. Hyd.	1800	0.56	750	9' 7"	14' 5"	NA	Lift
2	Standard Bucket	S 2212 II	-DO-	-DO-	Ind. Hyd.	1800 - 1950	0.56 - 0.65	1000	9' 7"	14' 5"	YES	Chassis
2A	Hi-Dump Bucket	S 2212 II	-DO-	-DO-	-DO-	1800	0.65	950	13' 7"	16' 3"	YES	-DO-
2B	6 In 1 Bucket	S 2212 II	-DO-	-DO-	-DO-	1750	0.65	950	11'	15' 2"	YES	-DO-
3A	Std. Bucket - Ditch Hoe	S 2216	-DO-	-DO-	-DO-	1800 - 1950 6.50/3.00	0.56 - 0.65 0.18/0.09	1000 ---	9' 7", 13' 4" Dig. Depth 8' 2"	14' 5" 18"	YES	NA
3B	Hi-Dump + Ditch Hoe	S 2216	-DO-	-DO-	-DO-	1800 6.50/3.00	0.65 0.18/0.09	950 ---	13' 7", 13' 4" Dig. Depth 8' 2"	16' 3" 18"	YES	NA

Multiple Application, Global Technology.....

RJMT

LOADERS - BACKHOES - GRADERS

INNOVATION FOR BETTER OUTPUT

POWERFUL ATTACHMENTS FOR SONALIKA TRACTORS

6 - In - 1 Bucket



LOADER S - 2219
STANDARD BUCKET

Counter Weight Mounted On 3 Point Link.
Loader Operated By Tractor Hydraulic System.

LOADER S - 2224

STANDARD BUCKET


3 Point Detachable
Counter Weight

Counter Weight Mounted On 3 Point Link.
Loader Operated By Tractor Hydraulic System.

Front End Loader For Construction Material And Solid Waste Handling

S.N	Attachments	Model	Tractor Reference H.P.	Drive	Hydraulic Operation	Bucket Inside Length (mm)	Rated Bucket Capacity (Cum)	Safe Working Load (kg)	Full Dump Height	Max. Opt. Height	Canopy YES/NO	Counter Weight On
1	Standard Bucket	S 2224	25-40	2WD	Tr. Hyd.	1500	0.3	300	7' 3"	11'	NA	Lift
1A	6 In 1 Bucket	S 2224	DO	DO	DO	1675	0.33	300	8' 8"	11' 4"	DO	DO
2	Standard Bucket	S 2219	38-50	-DO-	-DO-	1500	0.45	500	9"	13' 9"	-DO-	-DO-
2A	6 - In - 1 Bucket	S 2219	DO	DO	DO	1500	0.45	500	10' 4"	14' 2"	DO	DO



SEC-RJMT ENGINEERING PVT LTD.

Office : Plot No. 2, Pyala Road, Opp. - Shiv Mandir, Vill : Seelai, Mathura Road
Ballabgarh PIN : 121004, Faridabad (HR), Contact No. : 0129 - 2215050/40,
E-Mail : sales@secrjmt.com, secrjmt1@rediffmail.com
Website : www.secrjmt.com

All information are of general nature only (Variable \pm 2%). We reserve the right to change specification without any notice.

Low Cost, Low Maintenance, High Reliability, High Performance, Powerful Hydraulic System

